



Sleep Chair 1759-S

Overall Dimensions	32" w x 35" d x 33.5" h	Weight	150 lbs.
Seat Dimensions	25.5" w x 22" d x 18" h	Cubic Feet	29
Seat to Top of Back	20"	COM	8.25 yds.
Top of Arm to Floor	25"	Exposed Wood	
Extended Length	85.5"		
Sleep Surface Length	82		



Sleep Loveseat w/ Casters 1759-2SC

Overall Dimensions	53.5" w x 35" d x 33.5" h	Weight	185 lbs.
Seat Dimensions	47" w x 22" d x 18" h	Cubic Feet	49
Seat to Top of Back	20"	COM	10.25 yds.
Top of Arm to Floor	25"	Exposed Wood	
Extended Length	85.5"		
Sleep Surface Length	82		



Standard Features	Options Available
<ul style="list-style-type: none"> Multi-Position Steel Frame Mechanism Upholstered Arms, Seat and Back Tight Cushion Two 2" Locking Casters on Back, Two Non-Locking on Front of 1759-2SC Non-Marring Adjustable Glides 	<ul style="list-style-type: none"> Wood Arm Caps Black Poly Arm Caps Casters (1759-S only) CAL TB 133 Moisture Barrier

Standard Textile & Finish Selection

<http://carolina.ofs.com/design/textiles>
<http://carolina.ofs.com/design/finishes>

Frame Construction

Seat	<ul style="list-style-type: none"> Frame constructed of 5/4 WHND kiln dried maple
Back	<ul style="list-style-type: none"> Frame constructed of 5/4 WHND kiln dried maple
Arms	<ul style="list-style-type: none"> Top/bottom rail and front back post 5/4 WHND kiln dried maple Front post and top filler 8/4 WHND kiln dried maple Front/back top post 5/4 WHND kiln dried maple Top block 5/4 WHND kiln dried maple Bottom roll rail 5/4 WHND kiln dried maple
Assembly	<ul style="list-style-type: none"> Joints are assembled using glue, dowels, screws, and corner blocks The seat, back, arms and mechanism are assembled using 1/4" - 20 bolts and T-nuts No. 9 and No. 12 wood screws

Foam

Seat	<ul style="list-style-type: none"> 4 1/2" premium grade fire retardant foam 35 lb. compression 1.8 density Covered in 1.25 oz. of polyester fiber then cemented to the frame
Back	<ul style="list-style-type: none"> 2 1/2" premium grade fire retardant foam 30 lb. compression 1.8 density Covered in .75 oz of polyester fiber then cemented to the frame All foam is contour cut to fit the design