


Bariatric Chair 1441-OB

Overall Dimensions	34.5" w x 26" d x 33" h	COM 54"	2 yds.
Seat Dimensions	30" w x 18.5" d x 19" h	Shipping Weight	72 lbs.
Seat to Top of Back	14.25"	Cubic Feet	26
Top of Arm to Floor	25"	Exposed Wood	European Beech
Exposed Metal	Warm Grey Powder Coat		



Bariatric Chair 1441-K

Overall Dimensions	34.5" w x 26" d x 33" h	COM 54"	2 yds.
Seat Dimensions	30" w x 18.5" d x 19" h	Shipping Weight	72 lbs.
Seat to Top of Back	14.25"	Cubic Feet	26
Top of Arm to Floor	25"	Exposed Wood	European Beech
Exposed Metal	Warm Grey Powder Coat		



Standard Features	Options Available
<ul style="list-style-type: none"> • 500 lbs. weight rating (1441-OB) • 1000 lbs. weight rating (1441-K) • Clean-Thru design • Upholstered seat and back • Warm Grey (with Silver Ion Antimicrobial) powder coat on all exposed metal • Wall-Saver design • Non-marring adjustable glides • SCS Indoor Advantage Gold Certified • Limited lifetime warranty • QuickShip 	<ul style="list-style-type: none"> • Poly arm caps (black, grey or taupe) • Removable covers • Other powder coat options (does not include Silver Ion Antimicrobial) • Moisture barrier • Multiple textile application • CAL TB 133 Certified

Standard Textile & Finish Selection

<http://carolina.ofs.com/resources/textiles>
<http://carolina.ofs.com/resources/finishes>

Frame Construction

Seat	<ul style="list-style-type: none"> • Plywood seat EZ frame construction
Back	<ul style="list-style-type: none"> • Contoured plywood shape 11-ply
Frame	<ul style="list-style-type: none"> • 1" 16 gauge C1018 steel posts • 3/4" x 1/2" 12 gauge C1018 steel rails • Covered with European Beech hardwoods
Upholstery	<ul style="list-style-type: none"> • All fabric and leather pieces are cut with automated cutters that utilize precise patterns
Assembly	<ul style="list-style-type: none"> • All welded joints are full penetration mig/tig welds • All bolted connections are 1/4" - 20 grade 5 hardware

Foam

Seat	<ul style="list-style-type: none"> • 2.25" premium grade foam • CAL TB 117 Certified Fire Retardant • 55 lb. compression • 2.5 density
Back	<ul style="list-style-type: none"> • 1.5" premium grade foam • CAL TB 117 Certified Fire Retardant • 45 lb. compression • 1.8 density

Suspension

Seat	<ul style="list-style-type: none"> • LEXUS webbing <ul style="list-style-type: none"> • Polypropylene/latex/rubber
Back	<ul style="list-style-type: none"> • 2430 Propex <ul style="list-style-type: none"> • 100% Polypropylene • Latex coating is Paranol Acrylic 763 • Applied with 5/16" stainless steel staples