


Guest Chair 1441

Overall Dimensions	25" w x 26" d x 33" h	COM 54"	1.5 yds.
Seat Dimensions	21" w x 18.5" d x 19" h	Shipping Weight	60 lbs.
Seat to Top of Back	14.25"	Cubic Feet	20
Top of Arm to Floor	25"	Exposed Wood	European Beech
Exposed Metal	Warm Grey Powder Coat		



Standard Features	Options Available
<ul style="list-style-type: none"> • 400 lbs. weight rating • Clean-Thru design • Upholstered seat and back • Warm grey (with Silver Ion Antimicrobial) powder coated metal frame covered with European Beech wood accents • European Beech arm caps • Wall-Saver design • Non-marring adjustable glides • SCS Indoor Advantage Gold Certified • Limited lifetime warranty • QuickShip 	<ul style="list-style-type: none"> • Poly arm caps (black, grey or taupe) • Removable covers • Other powder coat options (does not include Silver Ion Antimicrobial) • Moisture barrier • Multiple textile application • CAL TB 133 Certified

Standard Textile & Finish Selection

<http://carolina.ofs.com/resources/textiles>
<http://carolina.ofs.com/resources/finishes>

Frame Construction

Seat	<ul style="list-style-type: none"> • Plywood seat EZ frame
Back	<ul style="list-style-type: none"> • Contoured plywood shape 11-ply
Upholstery	<ul style="list-style-type: none"> • All fabric and leather pieces are cut with automated cutters that utilize precise patterns
Frame	<ul style="list-style-type: none"> • 1" 16 gauge C1018 steel posts • 3/4" x 1/2" 12 gauge C1018 steel rails • Covered with European Beech hardwoods
Assembly	<ul style="list-style-type: none"> • All welded joints are full penetration mig/tig welds • All bolted connections are 1/4" 20 grade 5 hardware

Foam

Seat	<ul style="list-style-type: none"> • 2.25" premium grade foam • CAL TB 117 Certified Fire Retardant • 55 lb. compression • 2.5 density
Back	<ul style="list-style-type: none"> • 1.5" premium grade foam • CAL TB 117 Certified Fire Retardant • 45 lb. compression • 1.8 density

Suspension

Seat	<ul style="list-style-type: none"> • LEXUS webbing <ul style="list-style-type: none"> • Polypropylene/latex/rubber
Back	<ul style="list-style-type: none"> • 2430 Propex <ul style="list-style-type: none"> • 100% Polypropylene • Latex coating is Paranol Acrylic 763 • Applied with 5/16" stainless steel staples